

Specification Data Sheet

Hydroplank WPC Hybrid Flooring Click Profile for Floating Install, 1830 x 228 & 178 x 7.6mm

Hydroplank WPC Hybrid flooring represents next generation manufacturing techniques utilising sustainable Wood Plastic Composites (WPC) to form a robust, interior waterproof flooring. The visual décors provide realistic embossed timber textures and colours in both Australian timber species and a classic Oak palette. Hydroplank is coated with a matte finish, scratch resistant water-based PU lacquer for everyday scuff resistance.

The planks include a stabilising balance layer with an attached **1.5mm** cross-linked IXPE acoustic foam layer that delivers excellent noise reduction capabilities to enhance walking comfort and minimise sound transmission. **Interior use only.**

Key Features; Interior waterproof, can be installed in wet areas including bathrooms and laundry. Delivers superior dimensional stability. Excellent for renovations over existing ceramic tiles, minimal telegraphing. High impact **0.5mm** resistance wear layer. Two available plank widths, **Super Width 228mm** and **Classic Width 178mm**. Click for easy floating install.

Colour Range; Classic Australian Timber species, **178mm** & a contemporary colour Oak palette, **228mm**.

Description; Hybrid construction, WPC core, **0.5mm** Vinyl décor layer, with an attached **1.5mm** acoustic sound pad.

Grade & Surface; Slight embossed surface texture, matte sheen coating, non-toxic PU lacquer for everyday wear & tear.

Size & Length; **228mm** width, **7.6mm** thickness, **1830mm** length & **178mm** width, **7.6mm** thickness, **1830mm** length.

Quantity; **228mm** width, **2,504m²** / carton, approx. 64 cartons / pallet. **178mm** width, **1,920m²** / carton, approx. 85 cartons / pallet.

Profile; Click profile for floating install. **Micro Bevelled Edges.**

Acoustic outcome; Test Result including attached underlay, **LⁿT_w 43.**

Fire Test Data; AS/ISO9239.1-2003 (Flooring use) Critical Heat Flux, **5.3kW/m²**. Mean Smoke Development, **220 percent minutes.**

Slip Resistance; In accordance with AS/NZS 4586; 2013 **P4** for Wet Pendulum test & **R10** for the Oil-Wet Inclining test.

VOC Emissions; **E1**, (Below World Health Organisation Levels). **Hydroplank** is Respirable Silica Dust & Phthalate free.

Accessories; Alloy trims, MDF coloured scotia & Stair Nosing available to support colour selection for interior fit-out.

Please consult with your supplier for specific site install guidelines prior to installation. For specification or reseller support contact, info@preferencefloors.com.au or a local sales office.

www.preferencefloors.com.au

Adelaide (SA)

t +61 8 8262 2774
sa@preferencefloors.com.au

Brisbane (QLD)

t +61 7 3875 1688
qld@preferencefloors.com.au

Melbourne (VIC)

t +61 3 9794 5111
vic@preferencefloors.com.au

Perth (WA)

t +61 8 9471 7785
wa@preferencefloors.com.au

Sydney (NSW)

t +61 2 9738 1188
sales@preferencefloors.com.au