

Specification Data Sheet

Iconic WPC Hybrid Flooring Click Profile for Floating Install, 1520 x 228 x 7.5mm & 1520 x 180 x 7.5mm

ICONIC WPC Hybrid flooring represents next generation manufacturing techniques utilising a sustainable composites (WPC) core to form a robust, interior water-resistant flooring. The visual décors provide realistic timber textures and colours in both Australian timber species and a classic Oak palette. ICONIC is coated with a matte finish, scratch resistant, water-based PU lacquer for everyday scuff resistance.

The planks include a stabilising balance layer with an attached **1.5mm** cross-linked IXPE acoustic foam layer that delivers excellent noise reduction capabilities to enhance walking comfort and minimise sound transmission. **Product must be installed with 200µm Builder's Plastic on all substrates, do not fill expansion gaps with caulking/silicone. Please check local building authorities for interior wet area installation.**

Key Features; Excellent for renovations over existing ceramic tiles, minimal telegraphing. Interior water-resistant & high impact resistant **0.5mm** Vinyl wear layer. Click profile for easy floating install. Two plank widths, **Super Width 228mm** and **Classic Width 180mm**.

Colour Range; Classic Australian Timber species (not embossed), **180mm** & a contemporary colour Oak palette, (embossed) **228mm**.

Description; Hybrid construction, WPC core, **0.5mm** Vinyl décor layer, with an attached **1.5mm** acoustic sound pad.

Grade & Surface; Oak colours, embossed surface texture, matte sheen coating, non-toxic PU lacquer for everyday wear & tear.

Size & Length; **228mm** width, **7.5mm** thickness, **1520mm** length & **180mm** width, **7.5mm** thickness, **1520mm** length.

Quantity; **228mm** width, **2.080m²** / carton, approx. 76 cartons / pallet. **180mm** width, **2.189m²** / carton, approx. 70 cartons / pallet.

Profile; Angle / Angle Unilin Click for floating install. **Micro Bevelled Edges**.

Acoustic outcome; Test Result including attached underlay, **L'nT,w 39**.

Fire Test Data; AS/ISO9239.1-2003 (Flooring use) Critical Heat Flux, **9.6kW/m²**. Mean Smoke Development, **304 percent minutes**.

Slip Resistance; In accordance with AS/NZS 4586; 2013 **P3** for Wet Pendulum test & **R10** for the Oil-Wet Inclining test.

VOC Emissions; **E1**, (Below World Health Organisation Levels). ICONIC is Respirable Silica Dust & Phthalate free.

Accessories; Alloy trims, Moisture Resistant coloured Scotia & Stair Nosing available.

Please consult with your supplier for specific site install guidelines prior to installation. For specification or reseller support contact, info@preferencefloors.com.au or a local sales office.

www.preferencefloors.com.au

Adelaide (SA)

t +61 8 8262 2774
sa@preferencefloors.com.au

Brisbane (QLD)

t +61 7 3875 1688
qld@preferencefloors.com.au

Melbourne (VIC)

t +61 3 9794 5111
vic@preferencefloors.com.au

Perth (WA)

t +61 8 9471 7785
wa@preferencefloors.com.au

Sydney (NSW)

t +61 2 9738 1188
sales@preferencefloors.com.au