PREFERENCE FLOORS

Leading Brands, The Preferred Choice

Specification Data Sheet

Prestige Oak 190 x 14/2 mm. Tongue & Groove (T&G) and Click.

Prestige Oak planks are manufactured with a nominal 2**mm solid European Oak wear layer** permanently bonded to a nominal **12mm** mixed hardwood plywood substrate. This trusted method of construction provides a long wearing, stable and durable floor with a nominal finished thickness of **14mm**. Ideal for floors, ceilings & walls in residential, multi-residential and commercial construction projects. **Interior use only.**

Key Features; Engineered to exacting standards. Manufactured from sustained yield forest resources. Extremely stable with excellent wear resistance. Wear layer can be re-sanded and rejuvenated throughout the products lifecycle.

Colour Range; Natural oak, light Scandinavian tones, warm, earthy greys to darker colours.

Custom colours; Contract colours for multi-residential or commercial projects by arrangement, minimum volume requirements will apply.

Description; Engineered European Oak, **T&G** for direct fix, trowel adhesive installation or **Click** profile for floating installation.

Grade & Surface; A/B/C/D Grade contains knots and split defects that are filled and patched to compliment surface colour and character. Pre-finished Matte, German PU coating. Light wire brushed surface.

Nominal size & length; 190mm width, 14mm thickness, 1900mm length, approx. 30% nested shorter planks, 2 rows / carton, balance set length.

Quantity; 2.166m2 / carton, approx. **72 cartons** / pallet.

Profile; Tongue & Groove **(T&G)** or **Click,** Unilin Angle to Angle profile. Micro Bevelled Edges.

Acoustic outcome; Test Result with 2mm Underlay, **L'nT,w 42.**

Fire Test Data; AS/ISO9239.1-2003 (Flooring use) Critical Heat Flux, **3.7kW/m2**. Mean Smoke Development, **21 percent minutes.**

Slip Resistance; In accordance with AS/NZS 4586; 2013 **P3**. **VOC Emissions; E1**, (Below World Health Organisation Levels).

R-Value Thermal Resistance; 0.0875. JANKA Hardness; 5.5 – 6.0kN.

Accessories; Alloy trims, MDF coloured scotia & Stair Nosing available to support colour selection for interior fit-out.

Pre-finished, quick, and easy to lay - no dust, no smell, and no mess. Please consult with your supplier for specific site install guidelines prior to installation. For specification or reseller support contact, info@preferencefloors.com.au or a local sales office.

Adelaide (SA)
t +61 8 8262 2774
sa@preferencefloors.com.au

Brisbane (QLD)
t +61 7 3875 1688
qld@preferencefloors.com.au

Melbourne (VIC)
t +61 3 9794 5111
vic@preferencefloors.com.au

Perth (WA)
t +61 8 9471 7785
wa@preferencefloors.com.au

Sydney (NSW)
t +61 2 9738 1188
sales@preferencefloors.com.au