

## AB Grade Hardwood - Red Oak & White Ash – 190 x 14/3 x 1900mm

Our **HARDWOOD** COLLECTION is created using these two majestic Northern Hemisphere temperate hardwood species, **American Red Oak** and **White Ash from Central Asia**. These two hardwood species are used extensively throughout Europe and North America due to their natural beauty and performance characteristics.

We have curated 12 gorgeous colours that best fit the individual colour and grain patterns of Red Oak & White Ash. The engineered planks feature a **High - Spec AB grade** to deliver a stunning visual appearance that enhances the unique features of these two majestic species. **Less knots and natural features, for a cleaner look.**

HARDWOOD COLLECTION - T&G - 190 x 14/3 x1900mm - Hi-Spec - AB Grade					
Colour	Specie	Scotia	Trim	M2 / Ctn	M-Bevel V4
Forest Oak	Red Oak	Blackbutt	Latte	2.166	Yes
Frosty Snap	Red Oak	Alabaster	Silver	2.166	Yes
Golden Bloom	Red Oak	Blackbutt	Latte	2.166	Yes
Liberty Grey	Red Oak	Parana	Marble	2.166	Yes
Maple Falls	Red Oak	Crema	Parana	2.166	Yes
Nubuck	Red Oak	Blackbutt	Zermatt	2.166	Yes
Nutshell	Red Oak	Spotted Gum	Sunshine	2.166	Yes
Polar Fleece	Red Oak	Misty Cove	Parana	2.166	Yes
Autumn Leaves	White Ash	Spotted Gum	Sunshine	2.166	Yes
Spring Moon	White Ash	Ghost Gum	Parana	2.166	Yes
Summer Haze	White Ash	Zermatt	Parana	2.166	Yes
Winter Frost	White Ash	Misty Cove	Lugarno	2.166	Yes

**Features; High-Spec AB Grade, less knots and natural characteristics for a cleaner appearance.**

**Red Oak & White Ash are similar to our Australian Eucalyptus species; they are known for their light sensitivity; under exposure or over exposure to artificial or external UV light and heat may influence fading and colour change over time. Window & Door screening / protection is required, avoid placing rugs for approx. 8 weeks & reposition over time.** Please follow all install & care guidelines for warranty compliance.

**Installation;** optimum method is trowel spread, direct fix install. Floating method is also ok. Install on a dry & flat substrate. **Carefully follow all install guidelines that relate to the method installation, Direct Fix or Floating.**

**Profile; Tongue & Groove - Micro Bevelled Edges, 4 sides - Matte PU Lacquer coating. VOC: E1.**

**Sizes & Length; 190mm width x 14/3 mm thickness, 1900mm length - Nested Shorts.**

**Acoustic Test:** 14mm Engineered Timber over 2mm Green Underlay – **42 L'nT,w – 5 Star.**

**Fire Test:** AS/ISO 9239.1; 2003 -14mm Engineered Timber – **CHF, 5.9kW/m2, Smoke Value – 23% Minutes**

**Slip rating:** AS/NZS 4586; 2013. - **P3 for Wet Pendulum test.**

[www.preferencefloors.com.au](http://www.preferencefloors.com.au)