

Specification Data Sheet

Easi-Plank SPC Hybrid Flooring - Click Profile for Floating Install. 1520mm x 228 x 7.5mm & 1520 x 180 x 7.5mm.

Due to its unique stone polymer composite (SPC) construction and Vinyl wear layer, Easi-Plank flooring is a robust and highly durable choice for modern interiors. Easi-Plank visual décors feature realistic timber textures and colours in popular Australian Timber species and a contemporary Oak colour palette. Ideal for renovations or new interiors.

Easi-Plank Flooring is anti-static and resists common household stains & spillage. The planks include a balance layer with an attached **1.5mm** cross-linked IXPE acoustic foam pad that delivers excellent noise reduction capabilities, minimising sound transmission and enhances walking comfort. **Product must be installed with 200µm Builder's Plastic on all substrates, do not fill expansion gaps with caulking/silicone. Please check local building authorities for interior wet area installation.**

Key Features; Excellent for renovations over existing ceramic tiles, minimal telegraphing. Interior water-resistant & high impact resistant **0.5mm** Vinyl wear layer. Click profile for easy floating install.

Colour Range; Classic Australian Timber species **180mm** width, & a contemporary Oak colour palette, **228mm** width.

Description; Hybrid construction, SPC core, **0.5mm** Vinyl décor layer, with an attached **1.5mm** acoustic sound pad.

Grade & Surface; Oak colours embossed surface texture, matte sheen coating, non-toxic PU lacquer for everyday wear & tear.

Size & Length; **228mm** width, **7.5mm** thickness, **1520mm** length & **180mm** width, **7.5mm** thickness, **1520mm** length.

Quantity; **228mm** width, **1.733m²** / carton, approx. 48 ctns / pallet. **180mm** width, **1.642m²** / carton, approx. 45 ctns / pallet.

Profile; Angle / Angle Unilin Click for floating install. **Micro Bevelled Edges.**

Acoustic outcome; Test Result including attached **1.5mm** underlay, **L'nT,w 44.**

Fire Test Data; AS/ISO 9239.1-2003, Critical Heat Flux, **10.5kW/m²**. Mean Smoke Development, **90 percent minutes.**

Slip Resistance; In accordance with AS/NZS 4586; 2013 **P4** for Wet Pendulum test.

VOC Emissions; E1, (Below World Health Organisation Levels). **Easi-Plank** is Respirable Silica Dust & Phthalate free.

Accessories; Alloy trims, Moisture Resistant coloured Scotia & Stair Nosing available.

Please consult with your supplier for specific site install guidelines prior to installation. For specification or reseller support contact, info@preferencefloors.com.au or a local sales office.

www.preferencefloors.com.au

Adelaide (SA)

t +61 8 8262 2774
sa@preferencefloors.com.au

Brisbane (QLD)

t +61 7 3875 1688
qld@preferencefloors.com.au

Melbourne (VIC)

t +61 3 9794 5111
vic@preferencefloors.com.au

Perth (WA)

t +61 8 9471 7785
wa@preferencefloors.com.au

Sydney (NSW)

t +61 2 9738 1188
sales@preferencefloors.com.au