

Specification Data Sheet

ASPECT 72hr Water- Resistant Laminate 12MM - Click flooring for floating install only.

ASPECT 72hr Water- Resistant Laminate flooring provides realistic décor visuals with almost identical characteristics of natural timber planks. Using the latest digital imaging technology our Aspect range highlights popular Australian Timber species along with European Oak surface décors. Featuring class leading 72hr moisture protected treatment for the HDF Lo-Swell black core and the painted micro bevel edges, this water-resistant feature provides added reliability for when the unexpected does happen. Aspect laminate planks deliver all the charm & character you would expect from a natural timber floor with the added benefits of a Laminate: lower price, tough and durable, along with high moisture resistance suitable for everyday living.

ASPECT laminate is AC4 rated, making it tough enough and ideally suited for the wear and tear associated with modern family environments. It is dimensionally stable, exceptionally durable and offers great visual appeal for residential décors, and commercial fit-out.

Key Features; Manufactured with a Lo-Swell HDF Black Core. Extremely stable with excellent AC4 wear resistance rating.

Colour Range; 9 Colour decors including Blackbutt & Spotted Gum, 14 SKUs in total over various lengths & widths.

Description; 72hr Water – Resistant Lo-Swell Black Core laminate with a patented click profile for floating installation.

Surface; 12mm AC4 - scratch resistant performance. Smooth Matte coating Blackbutt & Spotted Gum, Oak decors EIR registered embossed surface.

Size & Length; 12mm – 2260 x 236mm - 2.13m² / carton. 2260 x 194mm - 1.75m² / carton. 1518 x 236mm – 1.79m² / carton.

Profile; Angle/Click profile. Painted Micro Bevelled Edges.

Acoustic outcome; Test Result with 2mm Green Underlay, 12mm - L'nT, w 45 & 8mm - L'nT, w 44.

Fire Test Data; AS/ISO9239.1-2003, 12mm CHF, 4.4 kW/m² & MSD, 12% minutes.

Slip Resistance; In accordance with AS/NZS 4586; 2013 P3. **VOC Emissions;** E1, (Below World Health Organisation Levels).

Swell Testing; Conforms to EN 13329:2016 + A1:2017 & ISO 24336:2005 & NALFA, T Seam - Swell & Seepage Test >80hrs.

R-Value Thermal Resistance EN 12996:2001; 12mm - 0.0730

Accessories; Alloy trims, MDF coloured scotia & Stair Nosing available to support colour selection for interior fit-out.

Pre-finished, easy to install - no dust, no smell, and no mess. Please consult with your supplier for specific site install guidelines prior to installation. For specification or reseller support contact, info@preferencefloors.com.au or a local sales office.

www.preferencefloors.com.au

Adelaide (SA)

t +61 8 8262 2774
sa@preferencefloors.com.au

Brisbane (QLD)

t +61 7 3875 1688
qld@preferencefloors.com.au

Melbourne (VIC)

t +61 3 9794 5111
vic@preferencefloors.com.au

Perth (WA)

t +61 8 9471 7785
wa@preferencefloors.com.au

Sydney (NSW)

t +61 2 9738 1188
sales@preferencefloors.com.au