PREFERENCE FLOORS

Leading Brands, The Preferred Choice

Specification Data Sheet

AB Grade Prestige Oak 220 x 21/6 mm. Tongue & Groove (T&G)

Prestige Oak AB Grade provides a visually appealing aesthetic to deliver a clean uncluttered décor. **AB Grade** planks are manufactured with a nominal **6 mm solid European Oak wear layer** permanently bonded to a nominal **15 mm** mixed hardwood plywood substrate. This trusted method of construction provides a long wearing, stable and durable floor with a nominal finished thickness of **21mm**. Ideal for floors, ceilings & walls in residential, multi-residential and commercial construction projects. **Interior use only.**

Key Features; Engineered to exacting standards. Manufactured from sustained yield forest resources. Extremely stable with excellent wear resistance. **AB Grade wear layer** can be re-sanded and rejuvenated throughout the products lifecycle.

Colour Range; A small range of colours from natural oak to light Scandinavian tones, **Raw (un-coated)** is also available for on-site staining & finishing.

Custom colours; Contract colours for multi-residential or commercial projects by arrangement, minimum volume requirements will apply.

Description; Engineered European Oak, Tongue & Groove for direct fix, trowel adhesive installation.

Grade & Surface; AB Grade may contain small tight knots, slight sapwood and natural oak colour variation. Minor colour matched surface filling can be evident to compliment surface colour and character. Pre-finished Matte, German PU coating. Certain colours light wire brushed, others smooth surface.

Nominal size & length; 220mm width, 21mm thickness, 2200mm length, approx. 25% nested shorter planks, 1 row / carton, balance set length.

Quantity; 1.936m2 / carton, approx. 40 cartons / pallet.

Profile; Tongue & Groove (T&G), Micro Bevelled Edges.

Acoustic outcome; Test Result with 2mm Underlay, **L'nT,w 45.**

Fire Test Data; AS/ISO9239.1-2003 (Flooring use) Critical Heat Flux, **5.5kW/m2**. Mean Smoke Development, **6 percent minutes.**

Slip Resistance; In accordance with AS/NZS 4586; 2013 **P3**. **VOC Emissions; E1**, (Below World Health Organisation Levels).

R-Value Thermal Resistance; 0.13125. **JANKA Hardness; 5.5 – 6.0kN.**

Accessories; Alloy trims, MDF coloured scotia & Stair Nosing available to support colour selection for interior fit-out.

Pre-finished, no dust, no smell, and no mess. Please consult with your supplier for specific site install guidelines prior to installation. For specification or reseller support contact, info@preferencefloors.com.au or a local sales office.

Adelaide (SA)
t +61 8 8262 2774
sa@preferencefloors.com.au

Brisbane (QLD)
t +61 7 3875 1688
qld@preferencefloors.com.au

Melbourne (VIC)
t +61 3 9794 5111
vic@preferencefloors.com.au

Perth (WA)
t +61 8 9471 7785
wa@preferencefloors.com.au

Sydney (NSW)
t +61 2 9738 1188
sales@preferencefloors.com.au